



J-FIX: BRICK TIES & HEAD RESTRAINTS

Brick Ties

J&P Cavity ties are manufactured to meet the requirements of BS DD140 Pts 1 & 2. Ties are readily available in Stainless Steel Grade 304 or Mild Steel Hot Dipped Galvanised unless stated otherwise. Ties are available with drip grooves (D), holes for dowels (H), full (FT) or half-twists (HT) and plastic sleeves (PS). Lengths shown are available in increments of 25mm. Special tie shapes/lengths available upon request. Minimum order quantity 250 No.




Head Restraints


J&P Sliding Brick Anchors are designed to provide the necessary restraint to the head of masonry panels. They allow for differential movement between the structural frame and cladding. Sliding brick anchors and associated sliding ties are available in stainless steel grade 304 or in mild steel with a hot dip galvanized finish.

Ties available single or double ended, with alternative tail shapes, with or without drip grooves, and in standard lengths.


Specials can be made to suit project requirements.



Type JPA/L
Fixed to a soffit frame



Type JPA/F
Fixed to the edge of a slab



Type JPA/T
Fixed to a soffit frame



J&P Concealed Blockwork Anchors are designed to restrain the head of internal masonry walls.

The stem is bolted to structural soffit and slides to required length in an outer casing, which in turn is bedded in blockwork coursing.

Available in stainless steel only

J-FIX: BRICK TIES & HEAD RESTRAINTS